




Produced with:
EXOSTENCIL[®]Screen Prep Paper

EXOSTENCIL[®] Screen Prep Paper

A revolutionary, environmentally friendly, “Chemical Free” way to make and reclaim screens. This simple, two step process eliminates the need for big investments, allowing you to get into production in just minutes. This process for manufacturing screens is appropriate for mesh counts from 85 – 230.

Equipment Needs: Laser Printer and a Heat Press



Imaging Sheet



Transfer Sheet

- Print image on paper with the **BROWN GRID** on the back
Note: Early manufacturing runs used “Yellow” ink on the back side of the Imaging Sheet. Everything else is the same as the “Brown” grid referenced here.
- Print image to be **RIGHT-READING**

HEAT
RIGHT-READING

EXOSTENCIL[®] SCREEN PREP PAPER INSTRUCTIONS



Design image



Print image negative
on EXOSTENCIL[®]
Screen Prep Paper



Transfer adhesive
to negative image



Place imaged area
against the underside
of screen



Print image

PRINTING INSTRUCTIONS:

1. Make a negative stencil-right facing image of the art to be screen printed. Include any alignment marks needed.
2. Use the ‘heavy paper’ setting to ensure fusing of the toners and ‘high resolution’ settings to ensure a continuous toner application. If not using an OKI[®] printer, printing the image with red or blue toner may result in a better image.
3. Inspect the EXOSTENCIL[®] Sheet for areas of damaged coating resulting from mishandling (these areas will create voids in the stencil).
4. Load the EXOSTENCIL[®] Screen Prep Paper with the brown grid on the back so that the image will appear on the plain, unprinted side of the paper and with the short dimension feeding into the printer (grain long).

OKI[®]
SUPPORTED



IMPORTANT: If not using an OKI[®] Printer, inspect the printed sheet with intense back lighting to ensure continuous toner application as voids in the toner will result in voids in the stencil. Pinholes indicate printer settings need to be adjusted to increase toner application. Toner adhesion can be tested by gently rubbing the image with a tissue. Note: If toner comes off, a different printer setting may be required.

APPLYING THE DRY ADHESIVE USING A HEAT PRESS:

1. Position the yellow grid transfer sheet face down over the printed image.
2. Position the image paper transfer sheet face up on the bottom platen of the pan.
3. Press: 25 seconds at 200°F/93°C with heavy pressure (70 psi/5 bar).
4. Separate papers in a smooth, even motion while still hot, taking care to not burn fingers.



Press Settings should be 200°F/93°C with 70 psi/5 bar pressure for 25 seconds

TRANSFERRING TO THE SCREEN USING A HEAT PRESS:

1. Place the 85 – 230 mesh count screen on the heat press, with the frame facing down.
2. Position the image face down on the screen to ensure all images align. Keep the image about 1" from press edges for best adhesion.
3. Press: 2 Minutes at 400°F/204°C, 60 psi/4 bar. If not using an OKI® printer, start at 2 minutes at 350°F/177°C.
Note: Obtaining desired adhesion may be challenging with some laser printers.
4. Allow the transfer paper to cool by waiving the screen in an up and down motion.
5. Peel the transfer paper away from the screen in one smooth motion.
6. Block the edges as you would with any screen.
7. Apply tape to spot repair any non-printed voids.
8. Use the screen stencil as you would an emulsion stencil.



Press Settings should be 400°F/204°C with 60 psi/4 bar pressure for 2 minutes

"CHEMICAL FREE" SCREEN CLEANING INSTRUCTIONS:

Pressure wash with at least 1500 PSI (103 bar), ensuring that the stencil is removed from all pores. Some harmless staining may remain.



Contact Us
888-740-6682 | info@NovaRhinstone.com

Shop
www.NovaRhinstone.com
2121 S. Main Street, Los Angeles, CA 90007
5849 W. 34th Street, Houston, TX 77092
7636 Harwin Dr. #105, Houston Tx 77036



MORE THAN 50%
MADE FROM RENEWABLE RESOURCES



NEENAH CONTROLS THE PROCESS
"FROM TREE TO T"™

